

Univerzalne stezaljke OT se koriste za povezivanje bakarnih i aluminijumskih provodnika sa sabirnicom. Konektori omogućavaju povezivanje jednog ili dva provodnika. Telo stezaljke i zavrtnaj za zatezanje su napravljeni od specijalne legure aluminijuma, a zatim

kalajisane. Površina zavrtnja koja ostvaruje kontakt premazana je kontaktnom pastom radi bolje provodnosti. Kontaktna površina takođe ima useke koji onemogućavaju izvlačenje provodnika.



OT 50



OT 95



OT 120



OT 150

	MAC1050E10	MAC1095E10	MAC1120E10	MAC1150E10
--	------------	------------	------------	------------

**Tehnički podaci**

Poprečni presek provodnika CU, AL (mm <sup>2</sup> )	1,5 - 50	6 - 95	16 - 120	25 - 150
Nominalni napon (V)	690	690	690	690
Nominalna struja CU / AL (A)	160 / 145	245 / 220	280 / 230	320 / 290
Širina / Visina / Dužina (mm)	14 / 21,5 / 35	20 / 30 / 46	25 / 35 / 64	26 / 39 / 62
Prečnik otvora (mm) AV / AV1	8,5 / 10,5	10,5 / 13	12,5 / 17	12,5 / 15
Zavrtnaj, inbus ključ	Br. 5	Br. 6	Br. 6	Br. 6
Snaga zatezanja (Nm)	3,5 Nm (1,5 - 10 mm <sup>2</sup> ) 12 Nm (16 - 50 mm <sup>2</sup> )	12 Nm (6 - 35 mm <sup>2</sup> ) 22 Nm (50 - 95 mm <sup>2</sup> )	12 Nm (6 - 35 mm <sup>2</sup> ) 25 Nm (50 - 120 mm <sup>2</sup> )	14 Nm (25 - 150 mm <sup>2</sup> ) 30 Nm (70 - 150 mm <sup>2</sup> )
Težina (g)	10	22	50	58
Pakovanje (kom)	30	30	30	20



OT 240



OT 300



OT 120-2



OT 240-2

	MAC1240E10	MAC1300E10	MAC2120E10	MAC2240E10
--	------------	------------	------------	------------

**Tehnički podaci**

Poprečni presek provodnika CU, AL (mm <sup>2</sup> )	35 - 240	95 - 300	2 x 25-120	2 x 70-240
Nominalni napon (V)	690	690	690	690
Nominalna struja CU / AL (A)	425 / 380	490 / 420	400 / 380	630 / 580
Širina / Visina / Dužina (mm)	32 / 44 / 74	32 / 48 / 64	26 / 62 / 74	38 / 70 / 99
Prečnik otvora (mm) AV / AV1	12,5 / 15	12,5 / 18	11 / 13	13 / 15
Zavrtnaj, inbus ključ	Br. 8	Br. 8	Br. 6	Br. 8
Snaga zatezanja (Nm)	26 Nm (35 - 120 mm <sup>2</sup> ) 40 Nm (150 - 240 mm <sup>2</sup> )	33 Nm (95 - 185 mm <sup>2</sup> ) 60 Nm (240 - 300 mm <sup>2</sup> )	10 Nm (25 - 35 mm <sup>2</sup> ) 20 Nm (50 - 120 mm <sup>2</sup> )	35 Nm (70 - 120 mm <sup>2</sup> ) 45 Nm (150 - 240 mm <sup>2</sup> )
Težina (g)	115	134	186	456
Pakovanje (kom)	10	10	10	10

**Dimenzije**

